

# SHARP

## NC2403ML/NC2003ML/NC1803ML Laser Projectors Digital Cinema Projector Series

### DCI-compliant laser light source projector

The NC2403ML/NC2003ML/NC1803ML features a built-in laser light source and is the ideal digital cinema projection solution for theaters with mid-sized screens or projection booths that are looking for high-quality cinema projection. This projector's reliability, maintenance-free operation and approximately 50,000\* hours of lifetime result in an overall lower total cost of ownership. The 2K DCI-compliant cinema quality means an outstanding image that is bright enough to display 14 ft-L on screens up to 72.0 ft./22m\*\* in DCI color.



### Newly designed laser light module

- The NC2403ML/NC2003ML/NC1803ML offers exhibitors an affordable and flexible new cinema projection solution thanks to its interchangeable laser light sources in the projector head for the ultimate in versatility and future-proofing
  - Higher reliability
  - Lower running cost due to savings of:
    - (a) No lamp replacement
    - (b) No maintenance labor
    - (c) No need of Stocking Lamps
- Redundancy and virtually maintenance free  
Quick laser replacement with easy slide-in for emergency -15 minutes!  
Exhibitors can minimize downtime if the laser light source needs to be changed
- Modular Light Source  
Starting with one (18,000 lumens) of three swappable laser light modules (24,000, 20,000 and 18,000 lumens), exhibitors can protect their investment by being able to display different content for different sized auditoriums with the same projector.
- Flexible installation  
The interchangeable laser light module can be purchased separately or leased for even more flexibility
- Highly flexible - as no exhaust system is required, the NC2403ML/NC2003ML/NC1803ML is suitable for floor and ceiling installation and versatile content playback
- Optimize cost of ownership  
Take advantage of new financing structures: lease laser light engine and only pay for the light exhibitors use

### Outstanding Performance

- Steady and reliable operation with lowered risk of black screen - Minimal downtime with the modular Laser Light Source.
- Longevity and lower maintenance provide for greater customer satisfaction with the introduction of the laser light source NC2403ML/NC2003ML/NC1803ML projector.
  - Enjoy lower TCO - up to 50,000\* hours of lifetime keeps costs to a minimum. You can enjoy better quality imaging while experiencing an overall lower cost of ownership. Brightness decreases in a linear fashion resulting in consistent image quality and greater satisfaction for your customers.
  - RB laser (NC2403ML/NC2003ML) system features red and blue lasers paired with phosphor to produce a rich color spectrum with unsurpassed brightness for the ultimate cinema experience.

### Super Dust Protection

- NEC's unique cooling system includes separate independent cooling sections for dust protection in both the optical engine and light source offering the best overall performance while providing theatre owners piece of mind

\*The life time may vary depending upon environmental conditions and does not constitute the warranty period.

\*\* Assuming 1.8:1 gain screen

**UNIQUE FEATURES**

**MINIMAL MAINTENANCE** Operation for approximately 50,000\* (under normal usage conditions) hours with long life of the light source.

**SIMPLE OPERATION** One touch operation, ergonomic keyboard layout and memory functions.

**MANY LENS OPTIONS** for easy installation.

**HIGH FRAME RATE (HFR) CAPABILITY** for outstanding picture quality.

**ACCESSORIES**

**Optional Lenses**

NC-60LS12Z, NC-60LS14Z, NC-60LS16Z,  
NC-60LS19Z, NC-60LS24Z, NC-60LS39Z

**ORDERING MODEL NUMBERS**

NP-NC2403ML: Laser light module built-in projector  
 NP-NC2003ML: Laser light module built-in projector  
 NP-NC1803ML: Laser light module built-in projector  
 NP-02HD: Projector head without laser light module  
 NP-24LU03: 24,000 lm laser light module  
 NP-20LU03: 20,000 lm laser light module  
 NP-18LU03: 18,000 lm laser light module



Model Number		NP-NC2403ML	NP-NC2003ML	NP-NC1803ML	
OPTICAL	Projection Method	3-chip DMD reflection method (DLP Light Engine)			
	Light Source	RB Laser Light Source		B Laser Light Source	
	DMD Specifications	0.98" DMD chip, DC mini 2K			
	Resolution	Native	2048 x 1080		
	Brightness (Lumens)	24,000	20,000	18,000	
	Light Source Life (up to)	50,000* hours			
	Supported Screen Size (width)***	Up to 72 ft. / 22m	Up to 65.6 ft. / 20m	Up to 62.3 ft. / 21m	
	Throw Ratio	NC-60LS12Z	1.20 to 1.80:1 zoom		
		NC-60LS14Z	1.40 to 2.05:1 zoom		
		NC-60LS16Z	1.59 to 2.53:1 zoom		
		NC-60LS19Z	1.90 to 3.25:1 zoom		
		NC-60LS24Z	2.40 to 3.90:1 zoom		
	NC-60LS39Z	3.90 to 6.52:1 zoom			
	Projection Distance	2.9 - 35.9 ft. / 0.9 - 10.9 m			
	Tilt Angle	+/- 15° (Up / Down)			
	Zoom	Motorized			
	Focus	Motorized			
	F-number, f-number	NC-60LS12Z	F=2.5, f= 26.7 - 40.5mm		
		NC-60LS14Z	F=2.5, f= 31.2 - 45.6mm		
		NC-60LS16Z	F=2.5, f= 35.4 - 56.4mm		
NC-60LS19Z		F=2.5, f= 41.6 - 71.1mm			
NC-60LS24Z		F=2.5, f= 52.4 - 85.3mm			
NC-60LS39Z	F=2.5, f= 84.9 - 142.0mm				
Lens Shift**	+/-23% Vertical, +/-7% Horizontal				
Cooling Method	Liquid cooling inside, air cooling with dust-preventing electrostatic filter				
CONNECTIVITY	Input Terminals	IMS	0		
	Output Terminals	IMS	0		
	External Control	IMS	0		
		Projector	1 x GPIO (3D) (D-sub 15 pin female); 1 x GPIO (D-sub 37 pin female); 1 X USB Type-A, 1 x RJ45 100Base-T, 1 X D-SUB 9-pin female-RS232C compliant		
ELECTRICAL	Power Requirements	100 - 240V AC, 50/60Hz Single Phase for Projector head 220 - 240V AC, 50/60Hz Single Phase for Light source			
	Input Current	18.1A	18.1A	18.1A	
	Power Consumption	3070	2792	2988	
	Heat Load (max. power)	10475	9526	10195	
	MECHANICAL				
	Product Dimensions (WxDxH)****	27.4 x 43.1 x 20.1 in. (697 x 1095 x 510mm)			
	Net Weight	330.8 lbs. / 150 kg Excluding lens		310.9 lbs. / 141 kg Excluding lens	
	Shipping Dimensions (WxDxH)	36.5 x 62.6 x 35.0 in. (926 x 1590 x 888 mm)			
	Gross Weight	600 lbs. (272 kg)		580 lbs. (263 kg)	
	Fan Noise	50dB			
ENVIRONMENTAL	Operating	Temperature	50-96°F / 10-35°C		
		Humidity	10 to 85% Humidity (Non-Condensing)		
		Altitude	0 to 3000 m (9,800 ft)		
	Storage	Temperature	14-122°F / -10 50°C		
		Humidity	10% - 85% (non-condensing)		
Altitude	0-12,000m / 0-39,370ft (above sea level)				
REGULATIONS	USA	UL60950-1, FCC Part15 ClassA (Marking: UL)			
	Canada	CAN/CSA C22.2, ICES-003 ClassA (Marking CAN ICES-3(A)/NMB-3(A))			
	Latin America	EN60950-1, EN55022 Class A, EN55032 CLASS A, EN55024, EN61000-3-2/-3-3/-3-11/-3-12 (Marking CE)			
	Laser Safety*****	USA	FDA 21 CFR 1040.10 and 1040.11, *Risk Group 3 according to Laser Notice 50		
Others		IEC60825-1 Ed3 2014 Class1, IEC62471-5 Risk Group3			
Limited Warranty (Parts & Labor)		Registered owners receive a 2-year parts and labor warranty			

\* The lifetime may vary depending upon environmental conditions and does not constitute the warranty period.

\*\* Lens Shift slightly varies depending on each lens.

\*\*\* Screen width may vary depending upon environmental conditions.

\*\*\*\* Without protrusions.

\*\*\*\*\* This product complies with performance standards for laser products under 21 CFR Part 1040 except with respect to those characteristics authorized by Variance Number 2015-V-3435 effective on April 7, 2016.

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. DLP Cinema and the DLP Cinema logo are trademarks or registered trademarks of Texas Instruments in the United States and other countries.



SHARP ELECTRONICS CORPORATION  
 100 Paragon Drive, Montvale, NJ 07645  
 1-800-BE-SHARP • <https://business.sharpusa.com>