

Digital Cinema Projector Series

NC2443ML/NC2043ML/NC1843ML 4K Laser Projectors

DCI-compliant laser light source projector

The NC2443ML/NC2043ML/NC1843ML features a built-in laser light source and is the ideal digital cinema projection solution for theaters with mid-sized screens or projection booths that are looking for high-quality cinema projection. This projector's reliability, maintenance-free operation and approximately 50,000* hours of lifetime result in an overall lower total cost of ownership. The 4K DCI-compliant cinema quality means an outstanding image that is bright enough to display 14 ft-L on screens up to 72.0 ft./22m** in DCI color.

Newly designed laser light module

- The NC2443ML/NC2043ML/NC1843ML offers exhibitors an affordable and flexible new cinema projection solution thanks to its interchangeable laser light sources in the projector head for the ultimate in versatility and future-proofing
 - Higher reliability
 - Lower running cost due to savings of:
 - (a) No lamp replacement
 - (b) No maintenance labor
 - (c) No need of Stocking Lamps
- Redundancy and virtually maintenance free
Quick laser replacement with easy slide-in for emergency -15 minutes!
Exhibitors can minimize downtime if the laser light source needs to be changed
- Modular Light Source
Exhibitors have the ability to protect their investment by being able to display different content for different sized auditoriums using the same projector with either of the two swappable laser light modules (24,000, 20,000 and 18,000 lumens).
- Flexible installation
The interchangeable laser light module can be purchased separately or leased for even more flexibility
- Highly flexible - as no exhaust system is required, the NC2443ML/NC2043ML/NC1843ML is suitable for floor and ceiling installation and versatile content playback
- Optimize cost of ownership
Take advantage of new financing structures: lease laser light engine and only pay for the light exhibitors use



Outstanding Performance

- Steady and reliable operation with lowered risk of black screen - Minimal downtime with the modular Laser Light Source.
- Longevity and lower maintenance provide for greater customer satisfaction with the introduction of the laser light source NC2443ML/NC2043ML/NC1843ML projector.
- Enjoy lower TCO - up to 50,000* hours of lifetime keeps costs to a minimum. You can enjoy better quality imaging while experiencing an overall lower cost of ownership. Brightness decreases in a linear fashion resulting in consistent image quality and greater satisfaction for your customers.
- RB laser (NC2443ML/NC2043ML) system features red and blue lasers paired with phosphor to produce a rich color spectrum with unsurpassed brightness for the ultimate cinema experience.

Super Dust Protection

- NEC's unique cooling system includes separate independent cooling sections for dust protection in both the optical engine and light source offering the best overall performance while providing theatre owners piece of mind

*The life time may vary depending upon environmental conditions and does not constitute the warranty period.

** Assuming 1.8:1 gain screen

UNIQUE FEATURES

MINIMAL MAINTENANCE Operation for approximately 50,000* (under normal usage conditions) hours with long life of the light source.

SIMPLE OPERATION One touch operation, keypad layout and memory functions.

MANY LENS OPTIONS for easy installation.

HIGH FRAME RATE (HFR) CAPABILITY for outstanding picture quality.

ACCESSORIES

Optional Lenses
 NC-60LS12Z, NC-60LS14Z, NC-60LS16Z,
 NC-60LS19Z, NC-60LS24Z, NC-60LS39Z

ORDERING MODEL NUMBERS

NP-NC2443ML: Laser light module built-in projector
 NP-NC2043ML: Laser light module built-in projector
 NP-NC1843ML: Laser light module built-in projector
 NP-42HD: Projector head without laser light module
 NP-24LU03: 24,000 lm laser light module
 NP-20LU03: 20,000 lm laser light module
 NP-18LU03: 18,000 lm laser light module



Model Number	NP-NC2443ML	NP-NC2043ML	NP-NC1843ML	
OPTICAL	Projection Method	3-Chip DLP Cinema		
	Light Source	RB Laser Light Source	B Laser Light Source	
	DMD Specifications	0.98" 4K		
	Resolution	Native	4096 x 2160	
	Contrast Ratio	2,000:1		
	Brightness (Lumens)	24,000	20,000	18,000
	Light Source Life (up to)	50,000* hours		
	Supported Screen Size (width)***	Up to 72 ft. / 22m	Up to 65.6 ft. / 20m	Up to 62.3 ft. / 19m
	Optional Lenses	NC-60LS12Z	1.20 to 1.80:1 zoom	
		NC-60LS14Z	1.40 to 2.05:1 zoom	
		NC-60LS16Z	1.59 to 2.53:1 zoom	
		NC-60LS19Z	1.90 to 3.25:1 zoom	
		NC-60LS24Z	2.40 to 3.90:1 zoom	
		NC-60LS39Z	3.90 to 6.52:1 zoom	
	Tilt Angle	+/- 15° (Up / Down)		
Zoom	Motorized			
Focus	Motorized			
Optional Lenses	NC-60LS12Z	F=2.5, f= 26.7 - 40.5mm		
	NC-60LS14Z	F=2.5, f= 31.2 - 45.6mm		
	NC-60LS16Z	F=2.5, f= 35.4 - 56.4mm		
	NC-60LS19Z	F=2.5, f= 41.6 - 71.1mm		
	NC-60LS24Z	F=2.5, f= 52.4 - 85.3mm		
	NC-60LS39Z	F=2.5, f= 84.9 - 142.0mm		
Lens Shift**	+/-23% Vertical, +/-7% Horizontal			
Cooling Method	Liquid cooling inside, air cooling with dust-preventing			
CONNECTIVITY	Terminals	1 x GPIO (D-sub 37 pin female); 1 X USB Type-A, 1 x RJ45 1000Base-T, 1 X D-SUB 9-pin female-RS232C compliant 1x IMB Slot(Series2 IMB compatible)		
	Power Requirements	100 – 240V AC, 50/60Hz Single Phase for Projector head 220 - 240V AC, 50/60Hz Single Phase for Light source		
ELECTRICAL	Input Current	19.1A	19.1A	
	Power Consumption	3182	2947	
	Heat Load (max. power)	10,857 BTU	10,056 BTU	
			10735 BTU	
MECHANICAL	Product Dimensions (WxDxH)****	27.4 x 43.1 x 20.1 in. (697 x 1095 x 510mm)		
	Net Weight	337 lbs. / 153 kg Excluding lens	317 lbs. / 144 kg Excluding lens	
	Shipping Dimensions (WxDxH)	36.5 x 62.6 x 35.0 in. (926 x 1590 x 888 mm)		
	Gross Weight	584 lbs. (265 kg)	564 lbs. (256 kg)	
	Fan Noise	50dB		
ENVIRONMENTAL	Operating	Temperature	50-96°F / 10-35°C	
		Humidity	10 to 85% Humidity (Non-Condensing)	
		Altitude	0 to 3000 m (9,800 ft)	
	Storage	Temperature	14-122°F / -10 50°C	
		Humidity	10% - 85% (non-condensing)	
		Altitude	0-9,144m / 0-30,000ft (above sea level)	
Regulations	USA	UL60950-1, 2nd Edition, 2014 / UL62368-1, 2nd Edition/ FCC Part15 Class A (ANSI C63.4.2014) (Marking: UL)		
	Canada	CAN/CSA C22.2, Np.60950-1-07, 2nd Edition, 2014, / ICES-003 Issue6 ClassA (Marking CAN ICES-3(A)/NMB-3(A))		
	Latin America	EN60950-1, EN55022 Class A, EN55032 CLASS A, EN55024, EN61000-3-2/-3/-3/-11/-3-12 (Marking CE)		
	Laser Safety*****	USA	IEC60825-1 Ed.3:2014 Class 1, IEC62471-5 :2015 Risk Group 3, Laser Notice No. 57	
		Others	IEC60825-1 Ed.3:2014 Class 1, IEC62471-5 :2015 Risk Group 3	
Limited Warranty (Parts & Labor)	Registered owners receive a 2-year parts and labor warranty			

* The lifetime may vary depending upon environmental conditions and does not constitute the warranty period.
 ** Lens Shift slightly varies depending on each lens.
 *** Screen width may vary depending upon environmental conditions.
 **** Without protrusions.
 ***** This product complies with performance standards for laser products under 21 CFR Part 1040 except with respect to those characteristics authorized by Variance Number 2015-V-3435 effective on April 7, 2016.

DLP Cinema and the DLP Cinema logo are trademarks or registered trademarks of Texas Instruments in the United States and other countries.
 All other brand or product names are trademarks or registered trademarks of their respective holders.
 ©2022 Sharp NEC Display Solutions of America, Inc. and the NEC logo are registered trademarks of NEC.