

## C501 Installation Guide

### 50" LCD Display

### Contents:

Product Description and Notes_____	Page 1
Tilt Angle and Rotation_____	Page 1
Ventilation Recommendations_____	Page 2
Display Dimensions_____	Page 3-4
Display Dimensions with stand_____	Page 5
Optional Table Top Stand Dimensions_____	Page 6
Dimensions of Optional Wall Mount (WMK-3255S)_____	Page 7
Control Codes_____	Page 8
Input Terminals_____	Page 9
Browser Control_____	Page 9



### Product Description

<b>Display Resolution</b>	C501
<b>Maximum Supported Resolution</b>	1920 x 1080 @ 60Hz
<b>Power Consumption (Typical)</b>	65W
<b>Power Consumption (Max Brightness)</b>	85W
<b>Power Consumption (Overall Max)*</b>	95W
<b>BTU's (Typical)</b>	221.79 BTU/hr
<b>BTU's (Max Brightness)</b>	290.03 BTU/hr
<b>BTU's (Overall Max)*</b>	324.15 BTU/hr
<b>Net Dimensions</b>	44.3 x 25.4 x 1.8 in. 1124.7 x 645.3 x 45.0mm
<b>Net Weight</b>	39.7lbs. / 18.0kg



\*Overall Max refers to when the unit is at max brightness the internal speaker is at max volume

### NOTES:

- This document is intended to be used as a reference guide to supply useful information for a design or installation. It is not intended to be a step-by step procedure for installation.
- Any ceilings or walls must be strong enough to support the monitor and the installation must be in accordance with any local building codes. All mounts should make secure contact to wood studs.
- 4:3 sources can be displayed on the 16:9 screen in either normal aspect ratio with bars on the left or right, or stretched horizontally to fill the screen using the menus (see "Aspect Modes" in menus and user manual).
- Distances are in inches, for millimeters multiply by 25.4.

### Tilt Angle and Rotation

Monitor may be angled and rotated from normal landscape and portrait orientation to both face up and face down positioning. Rotate only clockwise for portrait orientation. For Face Up or Face Down orientation, operating temperature must be <35C



## C501 Installation Guide


### 50" LCD Display

Rev 1.0

#### Ventilation Recommendations:

Dimensions below are recommended for proper ventilation when the unit is in a recessed area.

Operating Temperature:  
Landscape: 0– 40 C, 32– 104 F  
Portrait: 0– 40 C, 32– 104 F  
Face Up/Down: 0– 35 C, 32– 95 F



**NOTE:**


The ventilation space should not be covered or closed off at the front of the opening. If for some reason the opening needs to be covered, other means of ventilation will need to be incorporated into the design. Contact NEC for design review and recommendations.

## C501 Installation Guide

50" LCD Display

Rev 1.0

### Display dimensions:





## C501 Installation Guide

50" LCD Display

Rev 1.0

### Display dimensions (cont.):




## C501 Installation Guide

50" LCD Display

Rev 1.0

### Display Dimensions (with ST-401 stand):



**NOTE:**


The ST-401 optional stand attaches to the VESA hole pattern on the back of the display

## C501 Installation Guide

50" LCD Display

Rev 1.0

### Optional Table Top Stand Dimensions (ST-401):



**NOTE:**


The Pole of the ST-401 stand connects directly to the VESA hole pattern on the back of the display.

## C501 Installation Guide

50" LCD Display

Rev 1.0

### Dimensions of Optional Wall Mount Kit (WMK-4655S):



## C501 Installation Guide

### 50" LCD Display

Rev 1.0

### Control Codes:


Function (Monitor ID = 1)	Code Data
Power ON	01 30 41 30 41 30 43 02 43 32 30 33 44 36 30 30 30 31 03 73 0d
Power OFF	01 30 41 30 41 30 43 02 43 32 30 33 44 36 30 30 30 34 03 76 0d
Input Source Select DisplayPort	01 30 41 30 45 30 41 02 30 30 36 30 30 30 30 46 03 04 0d or 01 30 41 30 45 30 41 02 31 31 30 36 30 30 30 46 03 04 0d
Input Source Select HDMI1	01 30 41 30 45 30 41 02 30 30 36 30 30 30 31 31 03 72 0d or 01 30 41 30 45 30 41 02 31 31 30 36 30 30 31 31 03 72 0d
Input Source Select HDMI2	01 30 41 30 45 30 41 02 30 30 36 30 30 30 31 32 03 71 0d or 01 30 41 30 45 30 41 02 31 31 30 36 30 30 31 32 03 71 0d
Input Source Select HDMI3	01 30 41 30 45 30 41 02 30 30 36 30 30 30 38 32 03 78 0d or 01 30 41 30 45 30 41 02 31 31 30 36 30 30 38 32 03 78 0d
Input Source Select VGA (RGB)	01 30 41 30 45 30 41 02 30 30 36 30 30 30 30 31 03 73 0d
Input Source Select VGA (YPbPr)	01 30 41 30 45 30 41 02 30 30 36 30 30 30 30 43 03 01 0d
Input Source Select VIDEO	01 30 41 30 45 30 41 02 30 30 36 30 30 30 30 35 03 77 0d
Input Source Select MP	01 30 41 30 45 30 41 02 30 30 36 30 30 30 38 37 03 7D 0d or 01 30 41 30 45 30 41 02 31 31 30 36 30 30 38 37 03 7D 0d
Sound Mute ON	01 30 41 30 45 30 41 02 30 30 38 44 30 30 30 31 03 09 0d
Sound Mute OFF	01 30 41 30 45 30 41 02 30 30 38 44 30 30 30 32 03 0a 0d

**NOTE:** Contact your NEC rep for codes not listed.


### Cable Connection:

#### Communication Protocol:

Interface: RS-232C  
 Communication System: Asynchronous  
 Baud Rate: 9600 bps  
 Data Length: 8 bits  
 Parity: None  
 Stop Bit: 1 bit  
 Communication Code: ASCII



Interface: Ethernet (CSMA/CD)  
 Communication System: TCP/IP (Internet Protocol Suite)  
 Communication Layer: Transport layer (TCP)  
 IP Address: 192.168.0.10 (default out of box)  
 Port Number: 7142 (Fixed)



**NOTE:** If so desired, jumper "Request to send" and "Clear to Send" together on both ends of the cable to simplify cable connection. These connections are not required. The only connections required are pins 2 (TxD), 3 (RxD) and 5 (GND).



## C501 Installation Guide

50" LCD Display

Rev 1.0

### Input Panel (Bottom)



### Input Panel (Side - Rotated)



### Browser Control

Information and control can also be available through the HTTP browser control menu.

In order to accomplish this, type: **http://<the Monitor's IP address>/pd\_index.html**

Note that the LAN Power needs to be turned on in order for the display to be controlled while the units are off.

All displays are set to the IP address **192.168.0.10** as default. Note that Media Player has separate IP Address menu that can be accessed from the Monitor's menu or directly using separate IP Address. IP Address for Media Player is set to **192.168.0.110** for default configuration

Communicating network PC needs to be on the same subnet as display that is being communicated with

**NEC** C501 COMPUTE MODULE

- [HOME](#)
- [REMOTE CONTROL](#)
- [INPUT](#)
- [PICTURE](#)
- [AUDIO](#)
- [SCHEDULE](#)
- [MULTI INPUT](#)
- [OSD](#)
- [MULTI DISPLAY](#)
- [DISPLAY PROTECTION](#)
- [CONTROL](#)
- [SLOT2](#)
- [SYSTEM](#)
- [COMPUTE MODULE](#)
- [NETWORK \(CONTROL\)](#)
- [NETWORK \(MEDIA PLAYER\)](#)
- [MAIL](#)
- [SWMP](#)
- [AMX](#)
- [CRESTRON](#)
- [NAME](#)
- [NETWORK SERVICE](#)
- [PD LIST](#)
- [MEMO](#)
- [UPDATE FIRMWARE](#)
- [SD-CARD VIEWER](#)

HOME		
Welcome to the management and configuration web interface. You can use the navigation menus on the left to access additional pages.		
MONITOR INFORMATION		
MODEL NAME	C501	
SERIAL	6YP0007NA	
FIRMWARE VERSION		
REVISION	R0.042C	
ETHERNET (CONTROL)		
MAC ADDRESS	8c:df:9d:7f:4d:5f	
IPV4 ADDRESS	192.168.0.10	
SUBNET MASK	255.255.255.0	
DEFAULT GATEWAY	0.0.0.0	
DNS PRIMARY	0.0.0.0	
DNS SECONDARY	0.0.0.0	
ETHERNET (MEDIA PLAYER)		
MAC ADDRESS	8c:df:9d:7f:4d:60	
IPV4 ADDRESS	192.168.0.110	
SUBNET MASK	255.255.255.0	
DEFAULT GATEWAY	0.0.0.0	
DNS PRIMARY	0.0.0.0	
DNS SECONDARY	0.0.0.0	
ID		
MONITOR ID	1	
GROUP ID		
ECO CONTRIBUTION		
CARBON SAVINGS	0.527kg CO2	
CARBON USAGE	0.264kg CO2	
AUTO DIMMING	AUTO BRIGHTNESS	OFF
	ROOM LIGHT SENSING	OFF
	HUMAN SENSING	

Copyright © NEC Display Solutions, Ltd. 2016. All rights reserved.